


Magnetic catches

Magnet assembly to be clipped into aluminium profiles



Article number	L mm	B mm	b mm	H mm	Adhesive force* N	Weight g	Temperature °C	passend für Profile
MS041NdRe03K-00	41	6	9.5	10.2	10	4.5	80	30x30 Nut 6
MS041NdRe03K-03	41	6	9.5	10.2	18	9	120	30x30 Nut 6
MS041NdRe04K-00	41	8	11.6	9.3	18	6	80	30x30 Nut 8
MS041NdRe04K-01	41	10	13.7	13.2	18	7.5	80	45x45 Nut 10
MS041NdRe04K-02	41	8	12.5	12.9	18	7	80	40x40 Nut 8
MS041NdRe04K-07	41	8	11.6	9.3	30	10.5	120	30x30 Nut 8
MS041NdRe04K-08	41	10	13.7	13.2	30	12	120	45x45 Nut 10
MS041NdRe04K-09	41	8	12.5	12.9	30	11.5	120	40x40 Nut 8

APPLICATION:

Mounting rail magnets offer an easy fixing for doors, covers, metal housings, tools and accessories (for example at assembly workstations). Due to an easy mounting and the possibility of a fast dismantling these magnets are also useful with fair constructions.

PRODUCT INFORMATION:

The magnet assembly can be clipped into the groove. It is freely movable or can be fixed by a threaded pin. The magnetic core is protected by a plastic cover and has a large magnet area in the groove. The magnetic system is lying nearly plan and has a closed, smooth adhesive surface which avoids scratches on the surface and the concentration of metal shavings.

Alternative to the standard we also offer individual solutions:

- » Plastic housing in special colours
- » Temperature resistance up to 150°C

Packaging unit 10 pieces

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application

(installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes.

Let our experts advise you.