


Bar magnets of Neodymium-iron-boron (NdFeB)

Deep pot magnet made of NdFeB, steel housing, galvanised



Article number	D mm	H mm	A ¹ mm	Adhesive force* N	Weight g	Temperature °C
S4Nd	4 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	2.5	2	80
S5Nd	5 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	4.5	3	80
S6Nd	6 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	6	4.5	80
S8Nd	8 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	12	8	80
S10Nd	10 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	24	12	80
S13Nd	13 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	60	21	80
S16Nd	16 ^{+0.1} / _{-0.1}	20 ^{+0.2} / _{-0.2}	15	90	31	80
S20Nd	20 ^{+0.1} / _{-0.1}	25 ^{+0.2} / _{-0.2}	18	135	61	80
S25Nd	25 ^{+0.1} / _{-0.1}	35 ^{+0.2} / _{-0.2}	27	190	133	80
S32Nd	32 ^{+0.1} / _{-0.1}	40 ^{+0.2} / _{-0.2}	32	340	249	80

Our deep pot magnets are magnet systems with a cylindrical housing and impress with their high holding force. They are the perfect solution for machine, tool and fixture construction as well as for many other industries. They hold, clamp, transport and lift ferrous workpieces safely and reliably.

¹ Max. length by which the deep pot magnet can be shortened or machined without damaging it.

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.