

Decoration magnets metal body

Decoration magnet of hard ferrite, white lacquered, with hook



| Article number | D mm | HGes mm | Hook | Adhesive force* N | Weight g |
|----------------|------|---------|----------|-------------------|----------|
| DEMAG-16 | 16 | 25 | M3 | 18 | 7 |
| DEMAG-20 | 20 | 27 | M3 | 30 | 12 |
| DEMAG-25 | 25 | 30 | M4 | 40 | 23 |
| DEMAG-32 | 32 | 31 | M4 | 80 | 34 |
| DEMAG-36 | 36 | 31 | M4 | 100 | 45 |
| DEMAG-40 | 40 | 33 | M4 | 125 | 59 |
| DEMAG-47 | 47 | 34 | M4 | 180 | 89 |
| DEMAG-50 | 50 | 30 | M4 | 220 | 107 |
| DEMAG-57 | 57 | 33 | M4 | 320 | 149 |
| DEMAG-63 | 63 | 37 | M4 | 350 | 232 |
| DEMAG-80 | 80 | 55 | M6 (Öse) | 600 | 485 |

Alternative to the standard we also offer individual solutions:

- » Lacquering also possible in other colours
- » Equipped with a closed eyelet
- » Higher holding force

* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.